

View Online at <https://aerobasegroup.com/nsn/5930-00-613-4438>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.825 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.517 inches and 0.523 inches

Overall Height:

0.500 inches

Overall Width:

0.500 inches

Body Length:

Between 1.235 inches and 1.265 inches

Body Width:

Between 0.485 inches and 0.515 inches

Body Height:

Between 0.485 inches and 0.515 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.115 inches

Actuator Length:

Between 0.214 inches and 0.224 inches

Actuator Style:

Rectangular

Actuator Height:

0.025 inches

Actuator Width:

Between 0.225 inches and 0.255 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Switch Actuating Force:

Between 7.0 ounces and 14.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0