

View Online at <https://aerobasegroup.com/nsn/5930-00-613-4438>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.825 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.517 inches and 0.523 inches

**Overall Height:**

0.500 inches

**Overall Width:**

0.500 inches

**Body Length:**

Between 1.235 inches and 1.265 inches

**Body Width:**

Between 0.485 inches and 0.515 inches

**Body Height:**

Between 0.485 inches and 0.515 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

Between 0.100 inches and 0.115 inches

**Actuator Length:**

Between 0.214 inches and 0.224 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.025 inches

**Actuator Width:**

Between 0.225 inches and 0.255 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Switch Actuating Force:**

Between 7.0 ounces and 14.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0