NSN 5930-00-615-1397

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

3 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-00-615-1397

Overall Length:		
0.781 inches		
Center To Center Distance Between Mounting Facilities Parallel To Length:		
0.375 inches		
Overall Height:		
0.489 inches		
Overall Width:		
0.250 inches		
Body Length:		
0.781 inches		
Body Width:		
0.250 inches		
Body Height:		
0.396 inches		
Unthreaded Mounting Hole Diameter:		
0.088 inches		
Actuator Style:		
Round		
Actuator Diameter:		
0.092 inches		
Actuator Free Position Height:		
0.390 inches		
Maximum Voltage Rating In Volts:		
250.0 ac and 250.0 dc		
Inclosure Type:		
Fully enclosed		
Mounting Method:		
Unthreaded hole		
Nonpile-up Contact Arrangement:		
1 pole, double throw, one position momentary single switch unit		
Switch Release Force:		
1.0 ounces		
Switch Actuating Force:		
5.0 ounces		
Actuator Movement:		
Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches		
Contact Load Current Rating At Maximum Rated Voltage:		
5.000 amperes resistive dc and 5.000 amperes resistive ac		
Terminal Type And Quantity:		

NSN 5930-00-615-1397

Sensitive Switch - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0