

View Online at <https://aerobasegroup.com/nsn/5930-00-615-2956>

Thread Class:

3b single threaded bushing

Inside Diameter:

0.500 inches second connection

Thread Length:

0.438 inches single threaded bushing

Overall Length:

3.625 inches

Outside Diameter:

10.750 inches single connection

Overall Height:

3.125 inches

Body Diameter:

2.750 inches

Body Height:

3.125 inches

Distance Between Mounting Facility Centers:

1.500 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Base and threaded hole

Thready Qty Per Inch (tpi):

20 single threaded bushing

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.454 inches single threaded bushing

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

300.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

17.00 actuation point pounds per square inch and 15.00 deactuation point pounds per square inch and 2.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Tapered, butt weld second connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0