

View Online at <https://aerobasegroup.com/nsn/5930-00-615-2956>

**Thread Class:**

3b single threaded bushing

**Inside Diameter:**

0.500 inches second connection

**Thread Length:**

0.438 inches single threaded bushing

**Overall Length:**

3.625 inches

**Outside Diameter:**

10.750 inches single connection

**Overall Height:**

3.125 inches

**Body Diameter:**

2.750 inches

**Body Height:**

3.125 inches

**Distance Between Mounting Facility Centers:**

1.500 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Base and threaded hole

**Thready Qty Per Inch (tpi):**

20 single threaded bushing

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

150.00 pounds per square inch

**Thread Size:**

0.454 inches single threaded bushing

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Sensing Element Burst Pressure:**

300.00 pounds per square inch

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

2.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

17.00 actuation point pounds per square inch and 15.00 deactuation point pounds per square inch and 2.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Tapered, butt weld second connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0