

View Online at <https://aerobasegroup.com/nsn/5930-00-615-2961>

Body Style:

Hole mounted

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

Overall Height:

0.537 inches

Overall Width:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.356 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.018 inches and 0.028 inches

Actuator Height:

0.020 inches

Actuator Free Position Height:

0.330 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

4.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0