

View Online at <https://aerobasegroup.com/nsn/5930-00-615-3268>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

7.250 inches

**Overall Height:**

2.688 inches

**Overall Width:**

5.750 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket

**Thready Qty Per Inch (tpi):**

28 all pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

2.7 amperes resistive load first voltage and 1.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+4.00/+75.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

**Frequency In Hertz:**

60.0 single voltage

**Thread Series Designator:**

Unf all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0