NSN 5930-00-615-3269

Hazardous Locations/environmental Protection:

Pressure Switch - Page 1 of 2

Watertight

Overall Length: 5.500 inches
Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-00-615-3269

2.875 inches
Overall Width:
4.938 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Thread Size:
0.375 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
4.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+15.00/+90.00 actuation point pounds per square inch
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
115.0 dc at sea level second voltage
Frequency In Hertz:
60.0 single voltage
Thread Series Designator:
Npt single pressure connection

NSN 5930-00-615-3269

Pressure Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0