NSN 5930-00-615-4533

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-615-4533
Thread Class:
2b single pressure connection
Overall Length:
10.813 inches
Overall Height:
3.000 inches
Overall Width:
5.750 inches
Body Width:
4.250 inches
Unthreaded Mounting Hole Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
3.000 inches
Longest Vertical Distance Between Mounting Centers:
4.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
9.6 amperes resistive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+250.00/+3000.00 actuation point pounds per square inch gage and +250.00/+3000.00 deactuation point pounds per square inch gage
Contact Adjustment Type:

Contact Adjustment Type

External deactuation point hex nut and internal actuation point hex nut

NSN 5930-00-615-4533

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Pressure Connector Type: Plain, threaded internal single connection Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas, liquefied Style Designator: Rectangular w/bracket Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A048b0