

View Online at <https://aerobasegroup.com/nsn/5930-00-615-5147>

**Inside Diameter:**

0.500 inches single connection

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

6.230 inches

**Overall Height:**

3.100 inches

**Overall Width:**

4.750 inches

**Body Length:**

3.600 inches

**Body Width:**

4.000 inches

**Unthreaded Mounting Hole Diameter:**

0.265 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches

**Longest Vertical Distance Between Mounting Centers:**

3.100 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

14 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch

**Thread Size:**

0.500 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

6.0 amperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable, preset

**Contact Adjustment Range:**

+20.00/+100.00 actuation point pounds per square inch and +14.00/+94.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw with scale

**Contact Stimulus Rating:**

20.00 actuation point pounds per square inch and 6.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0