

View Online at <https://aerobasegroup.com/nsn/5930-00-615-5148>

Inside Diameter:

0.500 inches single connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

6.230 inches

Overall Height:

3.100 inches

Overall Width:

4.750 inches

Body Length:

3.600 inches

Body Width:

4.000 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

14 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+20.00/+100.00 actuation point pounds per square inch and +14.00/+94.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw with scale

Contact Stimulus Rating:

60.00 actuation point pounds per square inch and 6.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0