## NSN 5930-00-615-5751

Sensitive Switch - Page 1 of 2

8.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-615-5751

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
4.000 inches
Overall Height:
4.735 inches
Overall Width:
1.297 inches
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
2.844 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Housing Height:
2.156 inches
Housing Length:
2.750 inches
Housing Width:
1.156 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.625 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.250 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

## NSN 5930-00-615-5751

Sensitive Switch - Page 2 of 2

A053a0



Switch Actuating Force:
32.0 ounces
Actuator Movement:
Between 0.219 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 20.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: