## NSN 5930-00-615-6330

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-615-6330 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.125 inches **Overall Width:** 0.625 inches **Bushing Length:** 0.469 inches **Body Length:** 1.125 inches **Body Width:** 0.625 inches **Body Height:** 1.062 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Diameter:** 0.240 inches **Actuator Height:** Between 0.657 inches and 0.719 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.469 inches

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, both positions maintained single switch unit

## NSN 5930-00-615-6330

Toggle Switch - Page 2 of 2



Contact	Load Curre	nt Rating	At Maximum	Rated	Voltage:

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

2 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0