

View Online at <https://aerobasegroup.com/nsn/5930-00-615-6334>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.343 inches

Overall Height:

2.219 inches

Overall Width:

0.781 inches

Bushing Length:

Between 0.438 inches and 0.500 inches

Body Length:

Between 1.281 inches and 1.343 inches

Body Width:

Between 0.719 inches and 0.781 inches

Body Height:

1.062 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.657 inches and 0.719 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

End Application:

Guided missile, intercept

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 9.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0