

View Online at <https://aerobasegroup.com/nsn/5930-00-615-6799>

Body Style:

Bushing mount

Bushing Length:

Between 0.345 inches and 0.355 inches

Body Length:

0.500 inches

Body Width:

0.270 inches

Body Height:

Between 0.342 inches and 0.358 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.114 inches and 0.116 inches

Actuator Height:

Between 0.395 inches and 0.425 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

20.0 ac and 20.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 milliamperes resistive dc and 20.000 milliamperes resistive ac

Special Features:

Terminals 0.750 in. Lg

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0