# NSN 5930-00-615-6886

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-615-6886

### Thread Length:

0.250 inches single mounting facility

### **Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:** 

3.453 inches

#### First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.562 inches single actuator

**Overall Diameter:** 

1.000 inches

6

### **Individual Section Quantity:**

### **Switch Contact Basic Design:**

Nonpile-up symmetrical

### **Pole Quantity:**

1 each section front

# Throw Quantity:

7 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

115.0 ac at sea level

### **Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:** 

Round, flatted single actuator

Terminal Type:

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section rear

### **Switch Actuator Positioning Increment:**

36.0 degrees single actuator

### **Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

# NSN 5930-00-615-6886

Rotary Switch - Page 2 of 2



<b>Thread</b>	<b>Series</b>	Design	ator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0