

View Online at <https://aerobasegroup.com/nsn/5930-00-615-7036>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Width Between Flats:**

0.187 inches single actuator

**Overall Length:**

1.047 inches

**Overall Height:**

2.312 inches

**Overall Width:**

1.750 inches

**First Flat Length:**

0.141 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.234 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 6:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 6:00 o'clock

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Special Features:**

Number 6-32 tap by 1/4 in. Deep in shaft

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0