NSN 5930-00-615-7037



Lever Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-615-7037 **Body Style:** Hole mounted **Overall Length:** 4.641 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.531 inches **Overall Height:** 1.344 inches **Overall Width:** 0.719 inches **Body Length:** 3.266 inches **Body Width:** 0.719 inches **Body Height:** 1.344 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches **Actuator Style:** Round **Actuator Height:** 1.375 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position maintained **Actuator Position-locking Relationship:** Up position no locking action and down position no locking action and center position locked in **Maximum Voltage Rating In Volts:** 150.0 ac **Inclosure Type:** Uninclosed Thready Qty Per Inch (tpi): **Pile-up Contact Form Arrangement:** 1b1c 2nd position **Thread Size:** 0.099 inches **Contact Load Current Rating At Maximum Rated Voltage:** 1.000 amperes resistive ac **Thread Series Designator:** Unc

Terminal Type And Quantity:

8 tab, solder lug

NSN 5930-00-615-7037

Lever Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0