NSN 5930-00-615-7837

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-615-7837 **Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.781 inches **Overall Height:** 1.500 inches **Overall Width:** 1.188 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.875 inches single actuator **Nonturn Device Radius:** 0.438 inches at 9: 00 o'clock **Individual Section Quantity: Knob Manufacturer Code:** 71590 **Knob Manufacturer Part Number:** P120 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 6 single section rear **Mounting Method:** Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 dc at sea level

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round single actuator

NSN 5930-00-615-7837Rotary Switch - Page 2 of 2



| Terminal Type: |
|---|
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes single section rear |
| Switch Actuator Positioning Increment: |
| 60.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Adjustable stop single actuator |
| Contact Load Current Rating: |
| 1.75 amperes resistive load dc at sea level |
| Style Designator: |
| Circular wafer, bushing mount |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A052b0