

View Online at <https://aerobasegroup.com/nsn/5930-00-615-7880>

Body Style:

Bushing mount

Overall Length:

1.346 inches

Overall Height:

2.410 inches

Overall Width:

1.025 inches

Bushing Length:

0.470 inches

Body Length:

1.346 inches

Body Width:

0.430 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Missile minuteman Igm-30

Mounting Surface To Terminal End Distance:

1.250 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

18.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 11.000 amperes resistive ac and 8.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab w/screw

Specification Data:

96906-ms35059 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0