

View Online at <https://aerobasegroup.com/nsn/5930-00-615-7885>

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Submersible

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.797 inches and 1.827 inches

**Body Length:**

2.125 inches

**Body Width:**

1.380 inches

**Body Height:**

1.531 inches

**Unthreaded Mounting Hole Diameter:**

0.138 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.235 inches and 0.245 inches

**Actuator Height:**

Between 0.850 inches and 0.910 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Uh-1/c135/c130/h-3/seaking aircraft/los angeles/forrestal/nmitz/taaraw

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 22.000 amperes resistive ac and 15.000 amperes inductive ac and 3.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

9 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0