

View Online at <https://aerobasegroup.com/nsn/5930-00-615-7885>

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Submersible

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.797 inches and 1.827 inches

Body Length:

2.125 inches

Body Width:

1.380 inches

Body Height:

1.531 inches

Unthreaded Mounting Hole Diameter:

0.138 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

Between 0.850 inches and 0.910 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Uh-1/c135/c130/h-3/seaking aircraft/los angeles/forrestal/nmitz/taaraw

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 22.000 amperes resistive ac and 15.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Thread Series Designator:

Unc

Terminal Type And Quantity:

9 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0