

View Online at <https://aerobasegroup.com/nsn/5930-00-615-8895>

Thread Class:

2b and 2b

Body Style:

Bushing mounted

Body Diameter:

Between 0.619 inches and 0.625 inches

Bushing Length:

2.016 inches

Body Length:

0.470 inches

Actuator Diameter:

0.375 inches

Actuator Height:

0.250 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Aircraft phantom f-4

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A053a0