NSN 5930-00-615-8899

Rotary Switch - Page 1 of 2

Overall Height: 4.125 inches



View Online at https://aerobasegroup.com/nsn/5930-00-615-8899

| 1.120 1101100 |
|---|
| Overall Width: |
| 4.125 inches |
| First Flat Length: |
| 0.500 inches single actuator |
| Flat Height: |
| 0.312 inches single actuator |
| Shaft Diameter: |
| 0.375 inches single actuator |
| Shaft Length: |
| 0.875 inches single actuator |
| Individual Section Quantity: |
| 6 |
| Knob Manufacturer Code: |
| 82121 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Mounting Facility Circle Radius: |
| 1.609 inches single mounting facility |
| Mounting Method: |
| Bracket single mounting facility |
| Features Provided: |
| Actuator knob |
| Thready Qty Per Inch (tpi): |
| 20 single mounting facility |
| Thread Size: |
| 0.250 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 500.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position circular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 3 single actuator |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Makes before breaks, breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| Switch Actuator Positioning increment. |

NSN 5930-00-615-8899

Rotary Switch - Page 2 of 2



| Contact Load | Current | Rating: |
|--------------|---------|---------|
|--------------|---------|---------|

30.0 amperes resistive load ac at sea level

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0