NSN 5930-00-615-9281

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-615-9281

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
2.670 inches
Overall Height:
2.690 inches
Overall Width:
0.970 inches
Actuator Length:
1.380 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
2.530 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.125 inches
Housing Length:
2.000 inches
2.000 11.01.00
Housing Width:
Housing Width:
Housing Width: 0.970 inches
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts:
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type:
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method:
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided:
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal
Housing Width: 0.970 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.468 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.812 inches Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Features Provided: Actuator seal Nonpile-up Contact Arrangement:

128.0 ounces

Switch Actuating Force:

NSN 5930-00-615-9281

Sensitive Switch - Page 2 of 2



Δ	cti	Jato	r M	lov	em	en	ŧ.
м	LL	Jalu	'I IV	υv	em	СΠ	ш.

Between 0.100 pretravel inches and 0.219 overtravel inches and 0.065 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0