

View Online at <https://aerobasegroup.com/nsn/5930-00-615-9376>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Bushing Length:

Between 0.453 inches and 0.485 inches

Body Length:

1.346 inches

Body Width:

1.025 inches

Body Height:

Between 1.000 inches and 1.250 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 1.110 inches and 1.204 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

220.0 ac and 250.0 dc

End Application:

Strategic weapon system

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 9.000 amperes resistive ac

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0