

View Online at <https://aerobasegroup.com/nsn/5930-00-617-2087>

Thread Class:

3b single pressure connection

Inside Diameter:

0.250 inches single connection

Overall Length:

3.938 inches

Overall Height:

5.391 inches

Overall Width:

2.031 inches

Body Length:

3.219 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Tab w/screw

Contact Load Current Rating:

6.9 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+20.00/+50.00 actuation point pounds per square inch and +10.00/+70.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

35.00 actuation point pounds per square inch and 10.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Pressure Connector Type:

Inverted flare, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0