NSN 5930-00-617-2101

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-617-2101

| Overall Length: |
|---|
| 2.313 inches |
| Overall Height: |
| 2.812 inches |
| Overall Width: |
| 2.812 inches |
| First Flat Length: |
| 0.438 inches single actuator |
| Flat Height: |
| 0.188 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.688 inches single actuator |
| Individual Section Quantity: |
| 8 |
| Knob Manufacturer Code: |
| 10001 |
| Knob Manufacturer Part Number: |
| 9s5401l1 |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.297 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 7th section front |
| Throw Quantity: |
| 8 6th section front |
| Mounting Method: |
| Threaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 125.0 dc at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 8 single actuator |
| Shaft Type: |
| Round, flatted, threaded hole single actuator |
| Terminal Type: |
| Tab w/screw |

NSN 5930-00-617-2101

Rotary Switch - Page 2 of 2



| Contact Switching Action: |
|---------------------------|
|---------------------------|

Breaks before makes 8th section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0