

View Online at <https://aerobasegroup.com/nsn/5930-00-617-5048>

Hazardous Locations/environmental Protection:

Explosion resistant

Overall Length:

Between 4.490 inches and 4.510 inches

Overall Height:

Between 2.476 inches and 2.496 inches

Overall Width:

2.200 inches

Unthreaded Mounting Hole Diameter:

0.125 inches single mounting facility and 0.172 inches single mounting facility

Individual Section Quantity:

7

Longest Horizontal Distance Between Mounting Centers:

3.490 inches single mounting facility and 3.510 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.933 inches single mounting facility and 1.943 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Flange single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Features Provided:

Illuminated and legend plate

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

6 1st actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 7th section

Contact Arrangement Truth Table:

Decimal, 2 pole - 10 positions 1st section

Special Features:

Stop provided to limit actuator rotation on first section

Color:

White each indicator marking

Precious Material And Location:

Printed circuit board circuit surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0