NSN 5930-00-617-5131

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-617-5131					
Body Style:					
Panel mount					
Hazardous Locations/environmental Protection:					
Moisture resistant and salt spray resistant and shock resistant and vibration resistant					
Overall Length:					
0.750 inches					
Overall Height:					
3.407 inches					
Overall Width:					
0.750 inches					
Body Length:					
0.740 inches					
Body Width:					
0.740 inches					
Body Height:					
2.938 inches					
Actuator Length:					
0.740 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.250 inches					
Actuator Width:					
0.740 inches					
Actuator Color:					
Amber and green single actuator					
Illuminated Actuator Color:					
Amber and green single actuator					
Actuator Inscription:					
Test test single actuator					

Illuminated Actuator Color Sequence:

Upper half of actuator green lower half amber

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

NSN 5930-00-617-5131

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

P	racions	Matarial	And	Location:
_	recious	wateriai	Allu	LOCALION.

Contacts silver

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NO

Fiig:

A053a0