NSN 5930-00-617-5157

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-617-5157
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof and moisture resistant and salt water resistant and shock resistant and vibration resistant
Overall Length:
0.750 inches
Overall Height:
3.060 inches
Overall Width:
1.000 inches
Body Length:
0.750 inches
Body Width:
1.000 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
Amber and green single actuator
Illuminated Actuator Color:
Amber and green single actuator
Actuator Inscription:
Roll call/roll call single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator green lower half of actuator amber
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes
inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Contact surfaces silver and contacts gold

NSN 5930-00-617-5157

Push Switch - Page 2 of 2



	U	Ina	ıble	: To	De	COC	le:
--	---	-----	------	------	----	-----	-----

Unable to decode and unable to decode

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0