

View Online at <https://aerobasegroup.com/nsn/5930-00-617-7330>

**Body Style:**

Hole mounted

**Overall Length:**

Between 0.771 inches and 0.791 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.373 inches and 0.377 inches

**Overall Height:**

0.489 inches

**Overall Width:**

Between 0.240 inches and 0.260 inches

**Body Length:**

Between 0.771 inches and 0.791 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.355 inches and 0.375 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.082 inches and 0.102 inches

**Actuator Free Position Height:**

0.830 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**End Application:**

4general purpose electronic test equipment, helicopter search and rescue hh-60h, nimitz class cvn, forrestal class cv, helicopter uscg search and rescue hh-60j, aircraft f-111, helicopter mh-53e, helicopter carrier based asw sh-60f, aircraft phantom f-4

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

Between 3.0 ounces and 5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0