

View Online at <https://aerobasegroup.com/nsn/5930-00-617-7330>

Body Style:

Hole mounted

Overall Length:

Between 0.771 inches and 0.791 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

Overall Height:

0.489 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.355 inches and 0.375 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.082 inches and 0.102 inches

Actuator Free Position Height:

0.830 inches

Maximum Voltage Rating In Volts:

30.0 dc

End Application:

4general purpose electronic test equipment, helicopter search and rescue hh-60h, nimitz class cvn, forrestal class cv, helicopter uscg search and rescue hh-60j, aircraft f-111, helicopter mh-53e, helicopter carrier based asw sh-60f, aircraft phantom f-4

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

Between 3.0 ounces and 5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0