

View Online at <https://aerobasegroup.com/nsn/5930-00-617-8290>

**Thread Class:**

2b 1st mounting facility

**Thread Length:**

1.000 inches 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.563 inches

**Overall Height:**

2.188 inches

**Overall Width:**

2.500 inches

**Shaft Length:**

1.188 inches single actuator

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

80064

**Knob Manufacturer Part Number:**

9s540111

**Knob Specification Markings:**

Arrow

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 single section rear

**Throw Quantity:**

1 single section rear

**Mounting Facility Circle Radius:**

1.156 inches 1st mounting facility

**Mounting Method:**

Threaded stud 2nd mounting facility

**Features Provided:**

Actuator knob

**Thread Qty Per Inch (tpi):**

24 1st mounting facility

**Thread Size:**

0.190 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

120.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0