NSN 5930-00-617-8400

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-617-8400
Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.489 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.396 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.092 inches
Actuator Free Position Height:
0.615 inches
Actuator Adapter Style:
Roller leaf

Roller lear

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Missile, air to ground sidearm

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.016 overtravel inches and 0.031 differential inches

NSN 5930-00-617-8400

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0