NSN 5930-00-617-8400

Sensitive Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-617-8400 |
|---|
| Body Style: |
| Hole mounted |
| Overall Length: |
| 0.781 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.375 inches |
| Overall Height: |
| 0.489 inches |
| Overall Width: |
| 0.250 inches |
| Body Length: |
| 0.781 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.396 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.088 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.092 inches |
| Actuator Free Position Height: |
| 0.615 inches |
| Actuator Adapter Style: |
| Roller leaf |

Roller lear

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Missile, air to ground sidearm

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.016 overtravel inches and 0.031 differential inches

NSN 5930-00-617-8400

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0