# NSN 5930-00-617-9515

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-617-9515

View Online at https://aerobasegroup.com/nsn/5930-00-617-9
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.000 inches
Overall Height:
5.906 inches
Overall Width:
2.688 inches
Capillary Tube Length:
120.000 inches
Bulb Length:
3.000 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
2 406 inches

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Tempurature Sensing Element Type:

Capillary tube-bulb

**Operating Tempurature Rating:** 

150.0 degrees fahrenheit

#### **Mounting Method:**

Bracket

**Features Provided:** 

Tubing end seal connection

**Contact Action Stimulus:** 

Increase

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Tab w/screw

Contact Load Current Rating:

4.6 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

-10.00/+50.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

## NSN 5930-00-617-9515

Thermostatic Switch - Page 2 of 2



**Contact Voltage Rating In Volts:** 

550.0 dc at sea level third voltage

#### Frequency In Hertz:

60.0 single voltage

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A048b0