

View Online at <https://aerobasegroup.com/nsn/5930-00-618-5546>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.309 inches

Overall Height:

1.875 inches

Overall Width:

1.562 inches

First Flat Length:

0.428 inches single actuator and 0.448 inches single actuator

Flat Height:

0.216 inches single actuator and 0.220 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Nonturn Device Radius:

0.531 inches at 10: 30 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 10: 30 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 3rd section rear

Throw Quantity:

5 3rd section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 dc at sea level

Shaft Flat/slot Angular Location:

165.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 1st section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0