

View Online at <https://aerobasegroup.com/nsn/5930-00-618-6714>

Thread Class:

2a

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

Between 0.440 inches and 0.448 inches

Body Length:

Between 1.465 inches and 1.485 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.149 inches and 0.157 inches

Actuator Height:

Between 0.170 inches and 0.190 inches

Actuator Free Position Height:

Between 0.170 inches and 0.190 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.01 inch-ounces

Switch Actuating Force:

6.5 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.065 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc

Special Features:

Internally grounded to case

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0