

View Online at <https://aerobasegroup.com/nsn/5930-00-618-6714>

**Thread Class:**

2a

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

Between 0.440 inches and 0.448 inches

**Body Length:**

Between 1.465 inches and 1.485 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.149 inches and 0.157 inches

**Actuator Height:**

Between 0.170 inches and 0.190 inches

**Actuator Free Position Height:**

Between 0.170 inches and 0.190 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.500 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.01 inch-ounces

**Switch Actuating Force:**

6.5 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.065 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc

**Special Features:**

Internally grounded to case

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0