NSN 5930-00-618-6939

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-618-6939

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
4.376 inches
Overall Height:
2.906 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
D
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
2 each section front
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
125.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator

NSN 5930-00-618-6939 Rotary Switch - Page 2 of 2



Square Shaft Size:
0.375 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
20.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0