

View Online at <https://aerobasegroup.com/nsn/5930-00-619-4152>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.346 inches and 0.366 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Length:

0.844 inches

Actuator Style:

Leaf

Actuator Width:

0.130 inches

Actuator Free Position Height:

Between 0.408 inches and 0.512 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

7.0 grams

Switch Actuating Force:

45.0 grams

Actuator Movement:

Between 0.080 pretravel inches and 0.017 overtravel inches and 0.018 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0