

View Online at <https://aerobasegroup.com/nsn/5930-00-619-4445>

Overall Length:

Between 1.210 inches and 1.224 inches

Overall Height:

Between 0.608 inches and 0.648 inches

Body Diameter:

0.640 inches

Mounting Slot Width:

Between 0.140 inches and 0.154 inches

Body Height:

0.364 inches

Unthreaded Mounting Hole Diameter:

Between 0.140 inches and 0.154 inches

Distance Between Mounting Facility Centers:

Between 0.930 inches and 0.944 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

153.00 actuation point degrees fahrenheit and 163.00 actuation point degrees fahrenheit and 138.00 deactuation point degrees fahrenheit and 148.00 deactuation point degrees fahrenheit and 15.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0