

View Online at <https://aerobasegroup.com/nsn/5930-00-619-5403>

Thread Class:

2b single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.500 inches

Overall Height:

5.740 inches

Overall Width:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.209 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

100.00 pounds per square inch

Thread Size:

0.562 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+1.00/+27.00 actuation point pounds per square inch and +0.95/+26.75 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

50.0 first voltage and 60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0