NSN 5930-00-620-2844

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-620-2844 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 3.375 inches **Actuator Style:** Round **Actuator Diameter:** 0.750 inches **Housing Length:** 11.625 inches **Housing Width:** 3.375 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 8.375 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 2.375 inches **Maximum Voltage Rating In Volts:** 440.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed Thready Qty Per Inch (tpi): 16 **Thread Size:** 0.375 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Actuating Force:** 92.0 ounces **Actuator Movement:** 0.050 pretravel inches **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes inductive dc and 20.000 amperes inductive ac **Terminal Type And Quantity:** 6 wire lead Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5930-00-620-2844 Sensitive Switch - Page 2 of 2



Fiig:

A053a0