NSN 5930-00-620-2844

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-620-2844

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.375 inches

Actuator Style:

Round

Actuator Diameter:

0.750 inches

Housing Length:

11.625 inches

Housing Width:

3.375 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

8.375 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.375 inches

Maximum Voltage Rating In Volts:

440.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

16

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

92.0 ounces

Actuator Movement:

0.050 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes inductive dc and 20.000 amperes inductive ac

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-00-620-2844 Sensitive Switch - Page 2 of 2

Fiig: A053a0

