

View Online at <https://aerobasegroup.com/nsn/5930-00-621-3584>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

**Bushing Length:**

0.352 inches

**Body Length:**

0.652 inches

**Body Width:**

0.500 inches

**Body Height:**

0.527 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.410 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 24.0 dc

**Mounting Surface To Terminal End Distance:**

0.623 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Product Name:**

Switch, toggle 3 pole, subminiature, sealed

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0