NSN 5930-00-621-4537

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-621-4537
Hazardous Locations/environmental Protection:
Dustproof and moisture resistant and salt spray resistant and vibration resistant
Overall Height:
0.500 inches
Body Height:
0.364 inches
Overall Diameter:
0.640 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -80.0 degrees fahrenheit and 550.0 degrees fahrenheit
Mounting Method:
Surface
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load first voltage2.5 amperes resistive load second voltage1.0 amperes resistive load third voltage5.0 amperes
resistive load fourth voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
370.00 actuation point degrees fahrenheit and -100.00 deactuation point degrees fahrenheit and -65.00 deactuation point degrees
fahrenheit
Contact Voltage Rating In Volts:
30.0 ac at sea level first voltage125.0 ac at sea level second voltage250.0 ac at sea level third voltage30.0 dc at sea level fourth voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Disc

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5930-00-621-4537

Thermostatic Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A048b0