

View Online at <https://aerobasegroup.com/nsn/5930-00-621-5397>

Thread Length:

0.359 inches single mounting facility and 0.391 inches single mounting facility

Overall Length:

2.891 inches

First Flat Length:

0.922 inches single actuator and 0.954 inches single actuator

Flat Height:

0.216 inches single actuator and 0.222 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.734 inches single actuator and 0.766 inches single actuator

Overall Diameter:

1.250 inches

Nonturn Device Radius:

0.521 inches at 3:00 o'clock and 0.541 inches at 3:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

285.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0