NSN 5930-00-621-7227

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-621-7227

Thread Class:

2a single mounting facility

Thread Length:

0.427 inches single mounting facility and 0.447 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.394 inches

First Flat Length:

0.240 inches single actuator and 0.260 inches single actuator

Flat Height:

0.215 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.854 inches single actuator and 0.894 inches single actuator

Overall Diameter:

Between 1.155 inches and 1.185 inches

Nonturn Device Radius:

0.360 inches at 3: 00 o'clock and 0.390 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

6 single section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Push to turn

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

NSN 5930-00-621-7227Rotary Switch - Page 2 of 2



Rotor Through Connection Quantity:
2 single section
Switch Actuator Indexing Position Quantity:
6 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
250.0 milliamperes resistive load dc at sea level
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: